


BSV4140-0/16
Field-Wireable Connector
7/8" Male, Straight




Features



- For use in PROFIBUS-PA and FOUNDATION fieldbus applications
- Screw-clamp terminal
- Stainless steel coupling nut
- 4-pin
- PG16 screw-in thread
- Cable feedthrough 12.0...14.0 mm

Contact assignment



Headline Wiring Diagram
PROFIBUS-PA Connector FOUNDATION fieldbus connector



Technical data

Type	BSV4140-0/16
ID	6914541
Connector A	Male, 7/8"-16 UN, Straight
Number of pins	4
Contacts	Metal, CuZn, Gold-plated
Contact carriers	Plastic, TPU, Black
Connector body	Plastic, PA, Black
Coupling nut/screw	Stainless Steel, 1.4404, Passivated
Screw-in thread	PG16
External diameter of the cable	12...14 mm
Core cross-section/Clamping ability	0.14...1 mm²
Connection mode	Screw/clamp connection
Mechanical lifespan	> 100 Mating cycles
Pollution degree	3
Protection class	IP67
Network protocol	PROFIBUS-PA
Electrical properties at +20 °C	
Rated voltage	250 V
Current	9 A
Mechanical and chemical properties	
Ambient temperature (fixed)	-40...+90 °C
Ambient temperature (mobile)	-40...+90 °C
Note	
- We reserve the right to make technical modifications without prior notice.	