


FKW4.54-0.5

Accessories for Fieldbus Systems – Mounting Receptacle



Features




- Design: M12 female connector
- 5-pin
- PG9 mounting thread
- Reverse-keyed, 5-pin, stranded wire 0.5 m
- Front-mounted
- For use in PROFIBUS-DP applications
- Stranded wire length: 0.5 m

Technical data


Type	FKW4.54-0.5
ID	6935718
Connector A	Female, M12 × 1, Straight, B-coded
Number of pins	5
Contacts	Brass, CuZn, Gold-plated
Contact carriers	Plastic, TPU, Black
Seal	Plastic, FPM/FKM
Flange housing	Brass, CuZn, Nickel-plated
Mounting type	front panel mounting
Screw-in thread seal	Plastic, NBR
Screw-in thread	PG9
Connection mode	Wire connection
Mechanical lifespan	> 100 Mating cycles
Pollution degree	3
Protection class	IP67, (screwed together)
Network protocol	PROFIBUS-DP
Cable length	0.5 m
Core insulation	PVC
Core cross-section	5 x 0.34 mm²
Arrangement of strands	7 x 0.25 mm
Core colors	BN, GN, BU, RD, GY
Electrical properties at +20 °C	
Rated voltage	60 V
Current	4 A
Insulation resistance	≥ 10 ⁸ Ω
forward resistance	≤ 5 mΩ

Contact assignment




Headline Wiring Diagram

Pin Assignment



Front panel mounting



Technical data

Mechanical and chemical properties

Ambient temperature (fixed)	-30...+90 °C
-----------------------------	--------------
